-QIANYUE CASTER-

20 SERIES:HIGH TEMPERATURE WHEEL MEDIUM DUTY CASTER

1. made by imported Fiber glass nylon, its 20 - 30℃ higher and more resistant than domestic nylon and lifespan more longer

2. red color (290℃: no loading, 270℃: under loading), brown color (250℃ :no loading 230℃: under loading), black color (150℃ : no loading, 130℃ :under loading)

3. we offer free samples

20-S-NL

20-STB-NL

20-R-NL

20-T-NL

20-TB-NL

20-H-NL

20-HTB-NL

20-S-NL

20-STB-NL

20-R-NL

20-T-NL

20-TB-NL

20-H-NL

20-HTB-NL

20-S-NL

20-STB-NL

20-R-NL

20-T-NL

20-TB-NL

20-H-NL

20-HTB-NL

ITEM NO	diameterxwidth (mm)	plate size (mm)	bore hole spacing (mm)	Hole Size(mm)	Axle Size(mm)	Bore Hole Size(mm)	Total assembled Thickness + Mid-T	Total Height (mm)	Bearing	Screw (mm)	Spanner bushing (mm)	load capacity (KG)
3"	75x32	92x64	74x45	11.5x8.5	M12x30	M12	3/2.3	106	6001	M8/M10x52.5	40.5x9.5	90
4"	100x32	92x64	74x45	11.5x8.5	M12x30	M12	3/2.3	131	6001	M8/M10x52.5	40.5x9.5	100
5"	125x32	92x64	74x45	11.5x8.5	M12x30	M12	3/2.3	154	6001	M8/M10x52.5	40.5x9.5	110

CAD

3" Top plate rigid



3"Top plate swivel



3"Top plate swivel with brake



Product Advantage

- Complies with EU REACH and ROHS certification
- High quality-price ratio
- Passed 24 hours salt spray
- Adequate accessories and fast delivery
- Advanced equipment electroplating

Our Electroplating VS Traditional electroplatin

Our Electroplating	VS	Traditional electroplating
• Oil removal: Three processes to ensure thorough and stable oil removal	VS	• Oil removal: one process
• Pickling: Two processes ensure cleaner washing	VS	• Pickling: one process
• Increase chemical polishing to enhance electroplating brightness	VS	•
• Longer plating time, more than 1.5 hours double anode	VS	• 1 hour single anode
• The use of environmentally friendly water cleaning to meet environmental requirements	VS	• Use of common potion



Production & Delivery