-QIANYUE CASTER-

83XS SERIES:LOW PROFILE HEAVY DUTY CASTER

1. All-black industrial design: combines beauty and performance, suitable for high-end equipment and heavy-duty applications.

2. Sturdy welding process bracket: The structure is stable, the thickness is 5.5mm and it provides excellent impact resistance.

3. Stable locking function: After being rotated and fixed, it is not easy to loosen due to vibration, and it can maintain stability and reliability after long-term use.

83XS-S-NL

83XS-R-NL

83X-SLB-NL

83XS-STB-NL

83XS	diameterxwidth (mm)	plate size (mm)	bore hole spacing (mm)	Hole Size(mm)	Axle Size(mm)	Bore Hole Size(mm)	Hole size/bracket height (mm)	loading height (mm)	load capacity (KG)
2.5"	65x46	110x85	86x60	11	/	/	5.5/5.5	95	450
3"	75x46	110x85	86x60	11	/	/	5.5/5.5	105	500

CAD

3"Top plate swivel







Product Advantage

- Complies with EU REACH and ROHS certification
- High quality-price ratio
- Passed 24 hours salt spray
- Adequate accessories and fast delivery
- Advanced equipment electroplating

Our Electroplating VS Traditional electroplatin

Our Electroplating

- Oil removal: Three processes to ensure thorough and stable oil removal
- Pickling： Two processes ensure cleaner washing
- Increase chemical polishing to enhance electroplating brightness
- Longer plating time, more than 1.5 hours double anode
- The use of environmentally friendly water cleaning to meet environmental requirements

VS

Traditional electroplating

VS • Oil removal: one process

VS • Pickling： one process

VS • No increase in chemical polishing

VS • 1 hour single anode

VS • Use of common potion

Production & Delivery